



FS2021

URATOR - FALL ARREST HARNESS

The **FS2021 - Uurator** fall arrest harness is a full body harness for fall protection with a dorsal steel D-ring (EN361) and one chest D-ring (EN361). The FS2021 has four adjustment points, two on the chest with steel bar buckle and the others quick connect steel buckle on the legs. The 43mm polyester webbing contrast with the polyester grey seams. The webbing has two different colours to be easier to dress and position orientation.



EAN CODE	SIZE	WEIGHT (KG)	APPLICATIONS
5605423802801	UNIVERSAL	1 (aprox.)	Roof works Scaffolding Construction 
INTENSITY OF USE			STANDARDS
Occasional use <input checked="" type="radio"/> <input type="radio"/> <input type="radio"/>			 EN361:2002

FS2021 URATOR - FALL ARREST HARNESS

FEATURES



PHYSICAL PROPERTIES

Webbing 43 mm (black and orange)	Material 100% polyester Width (nom): 43.75 (+/- 1.25mm) Breaking Strength (min): 2300kg Weight (nom): 54g/m Thickness: 1.25mm Dye treatment: Disperse
Steel buckle	Stainless steel Breaking Strength (min): 9kN
Quick connection steel buckles	Stainless steel Breaking Strength (min): 9kN
D-rings (EN361)	Carbon steel (S45C) D-ring Breaking Strength (min): 22kN Thickness: 7.5 mm
Adjustment points	4 points
Fall arrest indicators	Yes
Thread (gray)	100% polyester Breaking force: 17850 cN (ISO DIN EN ISO 2062)
Thread (black)	100% polyester Tensile strength (ISO 2062): 4460 cN

OTHER INFORMATION

Device lifespan	10 years
Max. Load	<120 KG
Inspection requirement	Yearly
Traceability	Serial Number/ QR Code
Manual Instructions	www.fallsafe-online.com +351 252 480 060